

# PRODUCT DATASHEET

## Fiber Optic Splice Dome Closure Large 4 Tray 7 Inlet (6 Tray & 144 Core Capacity)

Single-ended, O-ring sealed dome closure for splicing feeder and distribution cables

- Compatible with most common cable types: e.g. loose tube, central core, ribbon fiber
- FOSC splice trays hinged for access to any splice without disturbing other trays
- Closure can be used in aerial, pedestal and underground (up to 5 meters) environments



### PRODUCT SPECIFICATIONS

Dimensions(mm)	220 X 435
Weight(Kg)	2.8
Diameter of Cable(mm)	7-22
No of Cable Inlet / Outlet	7
Number of Fibers per tray	24 (single core)
Max number of trays	6 (4 included in the box)
Max number of Fibers	144(single core)
Sealing of Inlet / Outlet ports	Heat-shrinkable tube
Sealing of shells	Silicon rubber
Storage Temperature Range	-40° C to 60° C

### KIT CONTENTS

Item	Type	Quantity
Fiber Optic Splice Sleeve		Allocated by the number of fibers
Buffer Tube	PVC	Allocated by the trays
Trays		4 Pcs
Heat-shrinkable tube	32 X 200	6 Pcs
Heat-shrinkable tube	70 X 250	1 Pcs
Branch Fork		1 Pcs
Marking Note		4 X cores of fiber cable
Hanging Tools	Aerial-hanging or wall-mounting	1 pair
Plastic hoop		1 Piece
Plastic wrench		2 small and 1 big
Seal ring		1 Piece
Sand paper		1 Piece
Aluminum paper		1 Piece